

C330M Cooled Infrared Detector

**Mature
Stable and Reliable**



Description

C330M is a mid-wave HgCdTe/MCT cooled infrared detector developed by Global Sensor Technology (GST). It is with the most classical 320x256/30 μ m spec and is among the earliest products in GST product portfolio. Configured with RS058/RS046H integrated stirling cooler, it can be used for almost all possible applications like long range surveillance system, handheld thermal imagers, gas leakage detection cameras etc.

Guarantee Continuous Supply

- Interchangeable standard interface
- Mass production, good consistency

Designed for Specific Applications

- Wavelength can be customized
- F number can be customized
- Mounting surface can be customized
- Multiple cryocoolers available

Specifications

Model	C330M MWIR
Sensitive Material	HgCdTe/MCT
Resolution	320×256
Pixel Size	30μm
Spectral Range	3.7μm±0.2μm ~ 4.8μm±0.2μm
Working Mode	Snapshot; ITR Integration Mode; Windows Mode; Anti-blooming
Charge Capacity	36Me-/12Me-
Dynamic Range	≥80dB
Number of Output	1 or 4; Up to 6.6 MHz per Output
Typical NETD	F2: 9mK F4: 15mK
Effective Pixel Rate	≥99.5%
Response Non-uniformity	≤8%
Cryocooler	RS058/RS046H
Steady Power Consumption	≤6W (RS058) ≤6W (RS046H)
Max. Power Consumption	≤12W (RS058) ≤11W (RS046H)
Power Supply	24V DC (RS058) 12V/32V DC (RS046H)
Cooling Time	≤6min (RS058) ≤5min30s (RS046H)
Weight	≤600g (RS058) ≤350g (RS046H)
Maximum Size (mm)	RS058: 142×58.5×71 RS046H: Compressor 45×35×68 Dewar φ33×75
Operating Temperature	-45°C ~ +71°C

Specifications are subject to change without prior notice.

Wuhan Global Sensor Technology Co., Ltd

+86 27 81298493

marketing@gst-ir.com

www.gst-ir.net

No. 6 Huanglongshan South Rd, Wuhan 430205, P.R.China